

ON-PREMISES LAUNDRY

Tumble Dryers

54.4 kg Tumble Dryer

77.1 kg Tumble Dryer

91.0 kg Tumble Dryer

Speed Queen®



THE BEST IN CLASS JUST GOT **BETTER.**

100 years. It's a long time for any company to be at the forefront of an industry. And you'd think that a company that's been able to lead for that long must have a finely honed craft — a premier product. Well, you'd be right. For more than a century, Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.



Some of our competitors may think that a residential machine wrapped in a rugged exterior passes for commercial grade. We believe that strength comes from within. Speed Queen machines are built specifically for the commercial environment. We use metal where others use plastic. Our world-class Test Lab rigorously pushes our products far beyond the conditions they'll face in the field. We believe in being there when our customers need us most. And we go the extra mile at every point of our manufacturing process to ensure that our machines reflect that belief.

For commercial laundry equipment designed for use in fire departments, health care facilities, hotels, correctional facilities, spas, salons, athletics organizations or another industry application, you can rely on the proven performance of Speed Queen to make your life simpler and more productive.

Made in America and refined for more than a century, Speed Queen Laundry equipment represents a secure investment for your on-premises laundry facility.

DEDICATED TO A HIGHER STANDARD

Uncomplicated. Uncompromising. Unmatched. Enjoy heavy-duty construction that will provide reliable operation for years to come.

Our single pocket tumble dryers feature a concentrated airflow pattern and sealed cylinder rims to ensure maximum air utilization and energy savings. This superior drying performance helps laundries maximize throughput to meet the daily workload without the need for added shifts or costly overtime. Our tumble dryers are designed with fewer moving parts, so that you'll face fewer maintenance problems and less wear and tear. We make it even easier with a large, easy-to-clean lint compartment and a heavy-duty door hinge designed to withstand heavy usage.

OVER-DRY PREVENTION TECHNOLOGY (OPT)

Reduce linen, labor and utility costs with the precise drying performance of OPT.

PRACTICAL INGENUITY

The Combustion Auto Response Equipped (C.A.R.E.) system alerts you to abnormally high temperatures in the cylinder and automatically sprays water in the cylinder to cool it down if necessary.

REVERSING CYLINDER

ensures even drying and prevents tangles for easy removal of loads.



EASY MAINTENANCE

Large, easy to clean lint compartment simplifies clean-up.

FASTER DRYING

High-performance heater box ignites instantly, increases energy efficiency and reduces drying times.

UNCOMPLICATED

Fewer moving parts means easier maintenance and less wear.

QUANTUM GOLD



Quantum Gold offers three modes of operation (time, auto and moisture dry) along with the flexibility of 30 programmable cycles and optional moisture sensing technology (OPT) that prevents over drying, saving time and energy.

DUAL DIGITAL



Set drying time, temperature and cool down. Features include one touch cycle repeat, automatic extended tumble and large digital countdown display.

Speed Queen®

ON PREMISES TUMBLE DRYER SPECIFICATIONS

| | | | | |
|---|-------------------------|---------------------------|---------------------------|---------------------------|
| Capacity - kg (lb) | | 54.4 (120) | 77.1 (170) | 91.0 (200) |
| Width - mm (in) | | 1178 (46 3/8) | 1349 (53 1/8) | 1349 (53 1/8) |
| Depth - mm (in) | | 1725 (67 15/16) | 1749 (68 7/8) | 1948 (76.68) |
| Height - mm (in) | Gas Models | 2177 (85 11/16) | 2388 (94) | 2388 (94) |
| | Steam Models | 2121 (83 1/2) | 2388 (94) | 2388 (94) |
| Cylinder Diameter - mm (in) | | 1118 (44) | 1289 (50 3/4) | 1289 (50 3/4) |
| Cylinder Depth - mm (in) | | 1041 (41) | 1080 (42 1/2) | 1270 (50) |
| Cylinder Volume - liters (cu. ft.) | | 1021 (36.1) | 1408 (49.7) | 1656 (58.5) |
| Door Opening Size - mm (in) | | 683 (26 7/8) | 683 (26 7/8) | 683 (26 7/8) |
| Energy Data | Gas Models - Per Pocket | 270,000 Btu/hr | 395,000 Btu/hr | 425,000 Btu/hr |
| | Steam Models - 100 psi | 405,000 Btu/hr | 648,000 Btu/hr | 648,000 Btu/hr |
| | Electric Models | 60 kW | | |
| Gas Supply Installation - mm (in) | | 25.4 (1) NPT | 25.4 (1) NPT | 25.4 (1) NPT |
| Steam Supply Installation - mm (in) | Inlet | 19.05 (3/4) NPT | 19.05 (3/4) NPT | 19.05 (3/4) NPT |
| | Outlet | 19.05 (3/4) NPT | 25.4 (1) NPT | 25.4 (1) NPT |
| Air Outlet - mm (in) | | 254 (10) | 305 (12) | 305 (12) |
| Rev. Motor - HP | Fan | 1 | 3 | 3 |
| | Cylinder | 3/4 | 3/4 | 3/4 |
| Airflow - liters/sec (cfm) | | 755 (1600) | 1156 (2450) | 1156 (2450) |
| Net Weight - kg (lb) | Electric /Gas | 578 (1275) | 714 (1575) | 790 (1741) |
| | Steam | 624 (1375) | 760 (1675) | 820 (1808) |
| Electrical Specs | Gas and Steam: | Amps | Amps | Amps |
| | 200-208/240/60/3 | 7.7 | 13.5 | 14.0 |
| | 380/60/3 | 4.1 | 6.6 | N/A |
| | 460-480/60/3 | 3.9 | 6.7 | 7.0 |
| | 380/400-415/50/3 | 3.8 | 6.9 | 8.0 |
| | Steam Only: | | | |
| | 440/60/3 | 3.8 | 6.4 | 7.0 |
| | Electric: | | | |
| | 240/60/3 | 152 | | |
| | 380/60/3 | 94.5 | | |
| | 480/60/3 | 76.1 | | |
| | 380/50/3 | 94.5 | | |
| | 400-415/50/3 | 87 | | |
| Shipping Weight - Standard - kg (lb) | Electric /Gas | 607 (1338) | 756 (1667) | 825 (1818) |
| | Steam | 656 (1446) | 806 (1776) | 855 (1885) |
| Shipping Width - mm (in) | | 1232 (48 1/2) | 1473 (58) | 1413 (58) |
| Shipping Depth - mm (in) | | 1829 (72) | 1892 (74 1/2) | 2019 (80) |
| Shipping Height - mm (in) | | 2286 (90) | 2515 (99) | 2515 (99) |
| Agency Approvals | Gas | cCSAus, CE, Australia Gas | cCSAus, CE, Australia Gas | cCSAus, CE, Australia Gas |
| | Steam | cCSAus, CE | cCSAus, CE | cCSAus, CE |

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

speedqueen.com/intl



Speed Queen®