

## ON-PREMISES LAUNDRY

### Softmount Washer-Extractors

18 lb Washer-Extractor    55 lb Washer-Extractor    135 lb Washer-Extractor  
25 lb Washer-Extractor    75 lb Washer-Extractor    165 lb Washer-Extractor  
35 lb Washer-Extractor    100 lb Washer-Extractor

**Speed Queen®**



# BUILT FOR **RELIABLE** PERFORMANCE.

100 years. It's a long time for any company to be at the forefront of an industry. And you'd think that a company that's been able to lead for that long must have a finely honed craft — a premier product. Well, you'd be right. For more than a century, Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.



Some of our competitors may think that a residential machine wrapped in a rugged exterior passes for commercial grade. We believe that strength comes from within. Speed Queen machines are built specifically for the commercial environment. We use metal where others use plastic. Our world-class Test Lab rigorously pushes our products far beyond the conditions they'll face in the field. We believe in being there when our customers need us most. And we go the extra mile at every point of our manufacturing process to ensure that our machines reflect that belief.

For commercial laundry equipment designed for use in fire departments, health care facilities, hotels, correctional facilities, spas, salons, athletics organizations or another industry application, you can rely on the proven performance of Speed Queen to make your life simpler and more productive.

Made in America and refined for more than a century, Speed Queen Laundry equipment represents a secure investment for your on-premises laundry facility.

# DEDICATED TO A HIGHER STANDARD.

The practical Ingenuity of Speed Queen is evident in every part of the heavy-duty suspensions and stainless steel construction. This is laundry for the modern world.

The powerful operation of a washer-extractor often requires that the machine be bolted to the floor. Softmount washer-extractors offer an alternative for specialized applications, such as second floors, where hardmount units aren't an option. They heavy duty suspension absorbs vibrations without the need for special foundations, and our stainless steel construction prevents the washer finish from corroding with normal use. The High G-force extraction significantly reduces drying times and utility costs, often removing significant moisture.

## VARIABLE SPEED DRIVE

Handles a wide variety of fabric types, while ensuring superior linen care/

## AUTOMATIC SUPPLY INJECTION

Reduces detergent waste, saves on labor costs and provides more consistent laundry results.



## SUPER HIGH EXTRACT SPEEDS

up to 475 G Force greatly reduce drying time and increasing throughput.

Speed Queen's Softmount Washer-Extractor Controls comes with 42 preset programs, expandable to 99 cycles, and the customizable wash programs help managers tailor their wash process for specific loads and linen types. The result? Your laundry receives the best possible care because operators have the utmost cycle control.

**Speed Queen®**

# SOFTMOUNT WASHER-EXTRACTOR SPECIFICATIONS

Models	SX18	SX25	SX35	SX55	SX75	SX100	SX135	SX165
Capacity - lb (kg)	18 (8.1)	25 (10.5)	35 (18.3)	55 (26)	75 (33.8)	100 (45.4)	135 (61.2)	165 (74.8)
Width - in (mm)	26" (660)	26" (660)	30 3/4" (780)	35 7/16" (900)	41 3/4" (1060)	47 1/4" (1200)	47 1/4" (1200)	51 1/4" (1300)
Depth - in (mm)	28 3/4" (730)	32 11/16" (830)	37 3/4" (960)	39 3/4" (1010)	46 1/16" (1170)	52 3/8" (1330)	59 1/16" (1500)	63 3/4" (1620)
Height - in (mm)	41 1/4" (1048)	41 1/4" (1048)	47 3/4" (1212)	60 1/2" (1538)	61 3/4" (1568)	75 9/16" (1920)	75 9/16" (1920)	82 11/16" (2100)
Cylinder Diameter - in (mm)	20 7/8" (530)	20 7/8" (530)	25 9/16" (650)	29 1/2" (750)	33 1/2" (850)	38 9/16" (980)	38 9/16" (980)	43 1/8" (1095)
Cylinder Depth - in (mm)	13" (330)	17 5/16" (440)	19 3/4" (500)	20 7/8" (530)	21 1/8" (537)	23 1/2" (597)	30 1/2" (775)	30 1/2" (775)
Cylinder Volume - cu. ft. (liters)	2.6 (73)	3.4 (95)	5.8 (165)	8.3 (234)	10.7 (304)	16.1 (455)	20.3 (575)	25.8 (730)
Door Opening Size - in (mm)	11 13/16" (300)	11 13/16" (300)	15 3/4" (400)	15 3/4" (400)	15 3/4" (400)	19 11/16" (500)	19 11/16" (500)	24 1/2" (622)
Wash Speed - RPM	10-50	10-50	10-50	10-50	10-50	10-50	10-50	10-50
Distribution Speed - RPM	85	85	85	69	65	61	61	100
Extract Speed - RPM	250-1000	250-1000	250-1000	250-1000	250-1000	250-800	250-800	250-750
Extract G-Force	296	296	362	418	475	350	350	344
Water Inlet Connection - in (mm)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	4 x 3/4" (19)	4" x 1 (25)
Steam Inlet Connection - in (mm)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	3/8" (10)	3/4" (19)
Drain Diameter - in (mm)	2" (50)	2" (50)	3" (75)	3" (75)	3" (75)	3" (75)	3" (75)	2 x 3" (75)
Motor Size - hp (kw)	1 (.75)	1 (.75)	3 (2.25)	4 (3)	5 (4)	7 (5.5)	10 (7.5)	15 (11.5)
Voltage/Hz/ Phase/Circuit Breaker	X 200-240/50-60/1-3	15	15	15	20	N/A	N/A	-
	Q 200-240/50-60/3	N/A	N/A	N/A	N/A	20	30	40
	P 380-415/50-60/3	N/A	N/A	N/A	N/A	15	20	25
	N 440-480/50-60/3	15	15	15	20	15	20	25
Shipping Dimensions Approx. - in (mm)	Width	28 3/4" (730)	28 3/4" (730)	33 7/16" (850)	38 3/16" (970)	44 1/8" (1120)	51 1/4" (1300)	51 1/4" (1300)
	Depth	33 1/16" (840)	37 13/32" (950)	40 5/32" (1020)	43 5/16" (1100)	49 5/8" (1260)	56 3/8" (1430)	64 1/4" (1630)
	Height	46 1/16" (1170)	46 1/16" (1170)	53 5/32" (1350)	66 15/16" (1700)	68 1/2" (1740)	79 1/8" (2130)	79 1/8" (2130)
Net Weight - lb (kg)	481 (218)	525 (238)	800 (363)	1177 (534)	1612 (731)	3521 (1597)	3940 (1787)	4960 (2250)
Shipping Weight - lb (kg)	525 (238)	569 (258)	889 (403)	1266 (574)	1722 (781)	3741 (1697)	4160 (1887)	5181 (2350)
Agency Approvals	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	CE, ETLus, ETLc	CE, ETLus, ETLc

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000. Printed in the USA.

[speedqueen.com](http://speedqueen.com)

